



Eco Bottle & Can

The best choice of cold drinks

The SandenVendo's fame stands for the reliable mechanism and the top quality of cooling unit for the cold drink models since 30's. The recent trend is coming back to the robust and simple yet functional column vendors, where SandenVendo is referred as a market leader.

The SandenVendo's traditional Bottle&Can went through a restyling and now presented in an elegant Design line, by upgrading with modern features and user-friendly interface.

In addition, always considering environmental sustainability, this line has been developed with HC (R290) Hydro Carbon version, pursuing the commitment to natural refrigerants.

XS-C36

B&C DESIGN C36 (XS)

	XS-C36
ABMESSUNGEN H x B x T (mm)	1830 x 650 x 800
NETTOGEWICHT (Standard-Gerät ohne Optionen)	280 Kg
AUSWAHLEN / SCHÄCHTE	6 / 6
MAX. PRODUKTLÄNGE (mm)	325
MAX. PRODUKT-DURCHMESSER (mm)	72
FASSUNGSVERMÖGEN DOSE 0,33 ltr.	306
FASSUNGSVERMÖGEN PET FLASCHE 0,50 ltr.	102
STEUERUNG	Executive / MDB
TEMPERATURKONTROLLE	Elektronisch
INNENTEMPERATUR	+1°C bis +25°C
MAX. LEISTUNGS-AUFNAHME	650 W
ELEKTROANSCHLUSS	230 V / 50 Hz



Eco Bottle & Can

The best choice of cold drinks

The SandenVendo's fame stands for the reliable mechanism and the top quality of cooling unit for the cold drink models since 30's. The recent trend is coming back to the robust and simple yet functional column vendors, where SandenVendo is referred as a market leader.

The SandenVendo's traditional Bottle&Can went through a restyling and now presented in an elegant Design line, by upgrading with modern features and user-friendly interface.

In addition, always considering environmental sustainability, this line has been developed with HC (R290) Hydro Carbon version, pursuing the commitment to natural refrigerants.

S-C47

B&C DESIGN C47 (S)

S-C47

ABMESSUNGEN H x B x T (mm)	1830 x 750 x 955
NETTOGEWICHT (Standard-Gerät ohne Optionen)	300 Kg
AUSWAHLEN / SCHÄCHTE	7 / 7
MAX. PRODUKTLÄNGE (mm)	325
MAX. PRODUKT-DURCHMESSER (mm)	72
FASSUNGSVERMÖGEN DOSE 0,33 ltr.	476
FASSUNGSVERMÖGEN PET FLASCHE 0,50 ltr.	238
STEUERUNG	Executive / MDB
TEMPERATURKONTROLLE	Elektronisch
INNENTEMPERATUR	+1°C bis +25°C
MAX. LEISTUNGS-AUFNAHME	700 W
ELEKTROANSCHLUSS	230 V / 50 Hz



Eco Bottle & Can

The best choice of cold drinks

The SandenVendo's fame stands for the reliable mechanism and the top quality of cooling unit for the cold drink models since 30's. The recent trend is coming back to the robust and simple yet functional column vendors, where SandenVendo is referred as a market leader.

The SandenVendo's traditional Bottle&Can went through a restyling and now presented in an elegant Design line, by upgrading with modern features and user-friendly interface.

In addition, always considering environmental sustainability, this line has been developed with HC (R290) Hydro Carbon version, pursuing the commitment to natural refrigerants.

M-C48

B&C DESIGN C48 (M)

	M-C48
ABMESSUNGEN H x B x T (mm)	1830 x 850 x 955
NETTOGEWICHT (Standard-Gerät ohne Optionen)	340 Kg
AUSWAHLEN / SCHÄCHTE	8 / 8
MAX. PRODUKTLÄNGE (mm)	325
MAX. PRODUKT-DURCHMESSER (mm)	72
FASSUNGSVERMÖGEN DOSE 0,33 ltr.	544
FASSUNGSVERMÖGEN PET FLASCHE 0,50 ltr.	272
STEUERUNG	Executive / MDB
TEMPERATURKONTROLLE	Elektronisch
INNENTEMPERATUR	+1°C bis +25°C
MAX. LEISTUNGS-AUFNAHME	700 W
ELEKTROANSCHLUSS	230 V / 50 Hz



L-C4X

Eco Bottle & Can

The best choice of cold drinks

The SandenVendo's fame stands for the reliable mechanism and the top quality of cooling unit for the cold drink models since 30's. The recent trend is coming back to the robust and simple yet functional column vendors, where SandenVendo is referred as a market leader.

The SandenVendo's traditional Bottle&Can went through a restyling and now presented in an elegant Design line, by upgrading with modern features and user-friendly interface.

In addition, always considering environmental sustainability, this line has been developed with HC (R290) Hydro Carbon version, pursuing the commitment to natural refrigerants.

B&C DESIGN C4X (L)

L-C4X

ABMESSUNGEN H x B x T (mm)	1830 x 1015 x 955
NETTOGEWICHT (Standard-Gerät ohne Optionen)	375 Kg
AUSWAHLEN / SCHÄCHTE	10 / 10
MAX. PRODUKTLÄNGE (mm)	325
MAX. PRODUKT-DURCHMESSER (mm)	72
FASSUNGSVERMÖGEN DOSE 0,33 ltr.	680
FASSUNGSVERMÖGEN PET FLASCHE 0,50 ltr.	340
STEUERUNG	Executive / MDB
TEMPERATURKONTROLLE	Elektronisch
INNENTEMPERATUR	+1°C bis +25°C
MAX. LEISTUNGS-AUFNAHME	700 W
ELEKTROANSCHLUSS	230 V / 50 Hz